

# TECHNICAL DATA BULLETIN



## OLYMPIC® Exterior Alkyd Lo-Sheen Finish 54691 Series

### PRODUCT DESCRIPTION

#### PRODUCTS

*Olympic* Exterior Alkyd Lo-Sheen Finish

54691 Pastel Base  
54692 Tint Base  
54693 Deep Base

#### TYPE

Oil-Alkyd Resin

#### RECOMMENDED USE

For use by Professional Authorized Factory Finishers and Professional Painters over wood, hardboard, oriented strand board and other wood based exterior surfaces. *Olympic* Lo-Sheen Finish provides an attractive low sheen finish and results in a tough mar and block resistant film.

#### TINTING

Can be tinted to most *Olympic* solid color paint and stain colors and *Machinecoat*® Pro-Mix colors. Additional *Pittsburgh*® Paints colors can be obtained by using the tint bases in conjunction with the *Pittsburgh* Paints Custom Colors. This system also allows for custom color matching to non-PPG colors.

#### SHEEN

Lo-Sheen

#### PERCENT SOLIDS BY WEIGHT

54691 71.73% ± 2.0%  
54692 71.06% ± 2.0%  
54693 70.24% ± 2.0%

#### PERCENT SOLIDS BY VOLUME

54691 51.45% ± 2.0%  
54692 51.37% ± 2.0%  
54693 51.37% ± 2.0%

#### ENVIRONMENTAL STATEMENT

These coatings are not formulated with any lead containing ingredients. These products comply with the Consumer Product Safety Commission "Ban of Lead Containing Paint" (16CFR1303).

The maximum Volatile Organic Content (VOC) of these products does not exceed 380 g/l (3.17 lbs/gal).

To obtain current VOC information on these or any *Olympic* product, call TOLL-FREE: 1-800-441-9695.

#### APPLICATION DATA

##### SURFACE PREPARATION

All surfaces must be clean and dry, and free from mildew, dust, oil, soot or other contamination.

Putty all nail holes and caulk all cracks and open seams. *MildewCheck*® Multi-Purpose Wash or an *Olympic* Deck Cleaner are recommended for cleaning mildewed or weathered surfaces before painting.

**New Wood:** Not recommended for finishing "green" wood with a moisture content of 19% or greater. This will increase dry-time, INHIBIT ADHESION, and may promote extractive bleeding and blistering.

**Previously Painted Wood:** Remove all loose, peeling, or flaking paint and old wood fibers by

scraping, chipping, or sanding. Sand all glossy surfaces. Thoroughly wash all chalky surfaces and areas protected from direct weathering, such as under eaves.

**WARNING:** Removing existing coatings from the surface to be painted by sanding, scraping or other mechanical means may create dust or particles containing lead, a hazardous substance. Avoid creating and breathing dust and other debris. Thoroughly clean all surfaces before and after painting. BREATHING OR EATING LEAD-CONTAINING DUST OR DEBRIS CAN CAUSE HEALTH PROBLEMS ESPECIALLY IN CHILDREN OR PREGNANT WOMEN.

In VOC regulated areas, primer and finish coats must comply with the regional VOC regulation.

##### MIXING DIRECTIONS

Stir thoroughly using a wide paddle or mechanical stirrer. To ensure all solids are agitated from the bottom of the container.

##### APPLICATION METHODS

Apply with approved Machine Application equipment, brush, flat pad applicator, or sprayer.

##### THINNING

NOT TO BE THINNED IN VOC REGULATED AREAS. In non-VOC regulated areas, if necessary, thin sparingly with a high quality paint thinner. Do not add oil.

##### DRYING TIME

77°F (25°C) 50% relative humidity  
Dust-Free: 1 to 2 hours  
To Touch: 4 to 6 hours